

Send us by fax or email: +33 (0)3 83 30 22 33 info@toshiba-lighting.com

CLIENT'S PRODUCT REQUEST

COMPANY DETAILS:	
Company name: Activity: Country: Web Site:	Contact name: Phone: Fax: Email:
WL ± 10 4 MAX. 11 MAX. CL OAL	FL 11 MAX.
LAMP SPECIFICATIONS*:	*please refer to brochure "Technical description"
Voltage:V Power:	W Filament Temperature:°Kelvin
Burning Position: Horizontal ☐ Universal ☐	
Lamp Type: JHS □ JHN JHC □ JHN JHB □ JHN JHA □ JHQ □ JHT □	IC 🗍 JHDSC 🗍 JHDMA 🗍 📗
Dimensions: Cables Terminal (If cables required):	
FL:mm Splice:	Faston Male:
CL:mm Fork M5: [WL:mm Ring M4: [☐ Cable insulation sleeve: Yes ☐ No ☐
Base Types: B □ Jc □ T B splashproof □ Rs □ Gw Bf □ N □ Gs J □ Ns □ Mag	Base Types jacketed lamps: B B B V IIIIIIIIIIIIIIIIIIIIIIIIIIIII
Packaging: Standard ☐ Individual ☐	
USEFUL INFORMATIONS:	
Application or system: Lamps annual consumption:Pcs Voltage, dimming during operation:% to% Quantity per delivery:Pcs Shock, vibration, acceleration: Yes No Cooling system on sealing part: Yes No	
COMMENTS:	